

Ubiquiti AirCam IP Camera 3 Pack



Product Name: Ubiquiti AirCam IP Camera 3 Pack

Manufacturer: -

Model Number: AirCam-3

Ubiquiti AirCam IP Outdoor Camera 3 Pack - H.264 megapixel camera

The Ubiquiti AirCam IP Camera 3 Pack is a high performance IP camera with a line of H.264 megapixel camera, which combines advanced industrial design, powerful performance with market leading cost-effectiveness. The Ubiquiti AirCam IP Camera 3 Pack has a number of advanced features which makes the model an ideal solution for video surveillance. Ubiquiti AirCam IP Camera Features

- Wall Mount/Ceiling Mount
- 30 FPS
- 1MP/HDTV 720p
- 4.0mm / F1.5
- Powered through Ethernet

Included with all units:

- Power Over Ethernet Adapter
- AirVision UI and NVR Software Installation CD

Ubiquiti Air Cam: Technical Specifications
Camera

- Ports: (1) 10/100 Ethernet
- Sensor: Progressive Scan RGB CMOS $\frac{1}{4}$ "
- Lens: 4.0mm/ F1.5
- Horizontal of View: 47°
- Ethernet Ports: Auto MDIX, autosensing 10/100 Mbps
- Power LED: Orange
- Link/Active LED: Green
- Buttons: Factory Reset Button
- Maximum Power Consumption: 2.4 Watts

Video

- Video Compression: H.264/MPEG-4/MJPEG
- Resolution: 1MP/HDTV 720p
- Maximum Frame Rate: 30 FPS
- Image Setting: Brightness, Contrast, Sharpness, Saturation, 50Hz/60Hz

General

- Processor: ARM-based 32-bit RISC
- Memory: 128MB DDR2 SDRAM, 8MB Flash
- Connector: RJ-45 10BASE-T/100BASE-TX PoE
- Maximum Active Array Size: 1280x800
- View Angle: 47°; (H), 31°; (V), 54°; (D)

Network

- Security: Multiple user access levels with password protection, User access log
- Supported Protocols: IPv4/v6, HTTP, UPnP, DNS, NTP, RTSP, DHCP, TCP, UDP, IGMP,

Ubiquiti AirCam IP Camera 3 Pack

RTCP, ICMP, ARP

Power

- Power Method: Passive Power over Ethernet (12-24V)
- Power Supply: 24V/0.5A PoE Adapter included

Physical

- Dimensions: 158 x 61.5 x 58.5 mm (without mounting arm), 264 x 61.5 x 58.5 mm (with mounting arm)
- Weight: 240 g (196 g without mounting arm)
- Mounting: Wall/Ceiling Adapter Kit included

Environmental

- Operating Temperature: -40 to 70°C (-40 to 158°F)
- Operating Humidity: 20 - 80% Noncondensing

Certification

- CE, FCC, IC

Please visit the Ubiquiti Firmware page for the latest Firmware upgrades
Also see the Ubiquiti Aircam Camera Management System

Price: £175.00
