VXI Passport 21v Headset QD1029 (Cisco 69xx, 79xx, 89xx,



Product Name: VXI Passport 21v Headset QD1029 (Cisco 69xx, 79xx, 89xx, 99xx)

Manufacturer: VXI Corporation
Model Number: VXIPP21VHSCIS

VXI Passport 21v Headset QD1029 (RJ9 with blue on cord)
The VXI QD1029 Passport 21v is compatible with all of the following IP phones:

• Cisco 6921, 6941, 6961, 794x, 796x, 797x, 8961, 9951, 9971

The VXi Passport 21V binaural single-wire headset incorporates the proven sound quality and durability of the Passport 20, with a lightweight design that is ideal for all-day use. Key Features

- Single-wire binaural. Single-wire design allows a greater range of motion for the user while being lighter weight and improving all-day wearing comfort
- Noise-canceling microphone. Available in all Passport headsets, the noise-canceling microphone ensures that only the user's voice is heard and not the background noise.
- Excellent receiver audio quality. High quality audio receivers, combined with the binaural design, ensure that the user hears the person on the other end of the call every time.
- Adjustable, flexible microphone boom. Gooseneck microphone boom design ensures constant and proper microphone placement.
- Durable construction withstands the constant demands of all-day use in contact centers
- Hearing protection. This feature helps to avoid sudden and unexpected sound spikes (such as fax machine noises).
- Warranty. 2-year warranty.

Transmit Specifications

- Microphone: Noise-canceling electret
- Ambient noise suppression: 15dB @ 1kHz, typical
- Output impedance : 2.2k O, typical
- Sensitivity: -42dbv/Pa@1cm
- Frequency response: 20Hz to 15kHz
- Operating current: 500µ A max. (200µ A for DC headsets)
- Operating voltage: DC 1.0V min. to 20V max.

Mechanical Specifications

- · Cables: Shielded wire, PVC insulation, polyurethane jacket
- Connectors: Gold-plated; quick disconnect
- Microphone boom: Flexible with positioning memory; swivels 300 degrees; left or right ear placement
- Headband: Nylon plastic and steel

Industry and regulatory certifications: FCC, CE, RoHS, WEEE Receive Specifications

Speaker: Dynamic, 36mm diameter
SPL: 98dB @ 1kHz, 0.55V input

• Impedance: 150O

• Frequency response: 200Hz to 4kHz

Price: £62.30