Xorcom Astribank 4 BRI 8 FXO 16 FXS (XR0098

Product Name: Xorcom Astribank 4 BRI 8 FXO 16 FXS (XR0098)

Manufacturer: Xorcom Model Number: XR0098

Xorcom Astribank-BRI Channel Bank (19" Chassis); 4 Basic Rate Interface ports 8 FXO 16 FXS Astribank is a PSTN channel bank and VoIP telephony system that was especially designed for the Asterisk open source IP-PBX. Astribank uses industry-standard USB 2.0 ports to communicate with the Asterisk server. Housed in an industry-standard 19" rack/wall-mountable chassis, a single Astribank supports up to 32 analog ports, or up to 144 analog and PRI channels. Hardware

• USB: External USB 2.0 port

Weight: 3 kg / 6.6 lbs

• Dimensions: Available in 19" 1U and 10" compact

• Mounting Options: Wall, Rack

BRI Module

- Full Euro ISDN support
- Programmable TE/NT settings for each channel
- Indicator lights for active settings and line status, per channel

FXS Module

- RJ11 connectors
- · Indicator lights for each channel
- Message indicator light support
- I/O ports: Input/Output ports for Asterisk peripheral device support
- TCO: P/N XR0034 Telecom Connector Option

FXO Module

- Worldwide impedance matching
- Flexible DC parameters
- Indicator lights for active settings and line status, per channel

Software The Astribank driver has been an official part of Zaptel (a.k.a. DAHDI) since release 1.2.4 in February 2006, making Astribank compatible with any standard Asterisk system.

Supported OS: Debian, CentOS 5 CentOS 4

Supported Asterisk Distributions: trixbox CE, Elastix

Price: £1,002.80