

Xorcom Astribank Dual PRI/R2 16 FXO 8 FXS (XR0079)



Product Name: Xorcom Astribank Dual PRI/R2 16 FXO 8 FXS (XR0079)

Manufacturer: Xorcom

Model Number: XR0079

Xorcom Astribank Channel Bank; Dual PRI 16 FXO 8 FXS

Astribank is a PSTN channel bank and VoIP telephony system that was especially designed for the Asterisk open source IP-PBX. Astribank uses industry-standard USB 2.0 ports to communicate with the Asterisk server. A single Astribank supports up to 32 analog ports, or up to 144 analog and PRI channels. Hardware

- USB: External USB 2.0 port
- Weight: 3 kg / 6.6 lbs
- Dimensions: Available in 1U and 10U; compact
- Mounting Options: Wall, Rack

E1/T1 PRI or E1 R2 Module

- Full PRI/R2 ISDN support
- NT/TE settings for each channel
- Indicator lights for active settings and line status, per channel
- E1/T1 support (configurable)

FXO Module

- Worldwide impedance matching
- Flexible DC parameters
- Indicator lights for active settings and line status, per channel

Software The Astribank driver has been an official part of Zaptel (a.k.a. DAHDI) since release 1.2.4 in February 2006, making Astribank compatible with any standard Asterisk system.

- Supported OS: Debian, CentOS 5 CentOS 4
- Supported Asterisk Distributions: trixbox CE, Elastix

Overview of Xorcom Network Topology

Xorcom Astribanks USB Based Telephony Modules for Asterisk

Xorcom IP PBX Product Lines & PBX Servers

Supported Extras Options

TwinStar Hot Failover

Price: £1,351.70

VoIPVN <http://voip.com.vn>