

Xorcom CXR2000 IP PBX with CompletePBX - 2 BRI, 16 FXS, 8 FXO, 2U Case (CXR2092)



Product Name: Xorcom CXR2000 IP PBX with CompletePBX - 2 BRI, 16 FXS, 8 FXO, 2U Case (CXR2092)

Manufacturer: Xorcom

Model Number: CXR2092

Xorcom CXR2000 IP PBX with CompletePBX - 2 BRI, 16 FXS, 8 FXO, 2U Case (CXR2092)

The CXR2092 features Xorcom's CompletePBX distribution and may be equipped with up to 2 BRI, 16 FXS and 8 FXO ports in a single 19" 2U chassis. The Xorcom CXR2092 supports up to 160 PSTN / Analog phones ports with external Astribank units, up to 200 users and up to 45 concurrent calls. This IP PBX is an Intel Atom® based stand-alone telephony solution with PSTN / telephone ports.

Xorcom CXR2092 IP-PBX Key Features

- Unlimited extensions, voicemail boxes, hunt groups, call center groups, and auto attendants (IVRs)
- Basic built-in call center with call recording, barge and whisper
- Emergency notification module
- Endpoint manager
- User-friendly Web interface
- Interface in different languages
- CDR (Call Details Record)
- TDM/SIP/IAX trunks
- Remote extensions
- Voicemail to email
- Web access to voicemail

Also available with the CXR2092 is the Xorcom Rapid Recovery™ backup utility, provided on Disk-on-Key. Xorcom CXR2000 units with an FXS module support Xorcom Rapid PA to provide public address functionality, and are also offered with I/O ports to support a wide array of peripheral devices.

Xorcom CXR2092 IP-PBX - Technical Specifications
Software

- Asterisk version - Xorcom's CompletePBX version 3.x
- Linux version -CentOS 6.2
- GUI Based on FreePBX (base version: 2.10)
- Security -Intrusion protection software; firewall protection
- Rapid Tunneling™; Utility providing secure remote access for product support purposes

Hardware

- Processor Intel Atom D2500 Dual Core 1.8 GHz
- RAM 2 GB
- Hard disk From 250GB 2.5" (500GB optional)
- Echo Cancellation Module
- Voice enhancement & echo cancellation (optional)
- Analog Lines Fail-over Kit In case of power outage or an Asterisk malfunction, up to six analog PSTN lines are routed directly to predetermined analog extensions (optional and model-specific)
- 4 external USB 2.0
- Input/Output ports for Asterisk peripheral device support (modelspecific)
- Rapid PA™; Public Address capability for FXS port(s) (optional and model-specific)

Xorcom CXR2000 IP PBX with CompletePBX - 2 BRI, 16 FXS, 8 FXO, 2U Case (CXR2092)

Telephony

- Maximum number of concurrent calls - 45
 - Maximum number of built-in analog ports - 32 (additional ports with external Astribank units)
 - Number of E1 / T1 ports -1 (up to 30 concurrent PRI/R2/CAS calls)
 - Maximum telephony modules supported internally -4 (additional Astribank ports are supported by adding Astribank units)
 - Maximum number of telephony ports supported internally 54 (E1 PRI/R2/CAS + 24 analog ports)
 - Supported Xorcom telephony modules
-
- 8 FXS ports
 - 8 FXS ports + I/O ports
 - 8 FXO ports
 - 2 FXO ports, 6 FXS ports + I/O ports
 - 6 FXO ports, 2 FXS ports
 - 1 PRI/R2/CAS port
 - Up to 8 BRI ISDN ports

Power

- Internal Power supply
- Voltage Switching, auto adjust 110/220 Volts, 50/60 Hz
- Power consumption 230 Watts (maximum)
- Built in grounding connection

Network

- Ethernet port 10/100/1000 Mb/s

Maintenance and Support

- Monitor and keyboard support
- Rapid Recovery[®]; backup utility provided on disk-on-key (optional)
- Rapid Tunneling[®]; utility providing secure remote access for product support purposes
- Internet updates

Environment

- Storage temperature -20[°]; to 70[°]; Celsius (-4[°]; -158[°]; F)
- Working temperature 0[°]; to 40[°]; Celsius (32[°]; -104[°]; F)
- Humidity 20%-95%, non condensing

Dimensions and Weight

- Weight 8 Kg 18Lbs (weight depends on configuration)
- Size 19" 2U industry standard rack-mountable chassis

Price: £1,863.00
