

# Y-cam White S POE IP Camera



Product Name: Y-cam White S POE IP Camera

Manufacturer: -

Model Number: YCWP04

## Y-cam White S POE IP Camera

The Y-cam White S POE is a versatile solution for home or business security, and can even operate outdoors using a Y-cam Shell. Using built-in movement sensors, the camera can instantly email you or upload snapshots, or video, to a website if motion is detected. Y-cam White S POE Features

- PoE Power Over Ethernet
- Secure Connection
- Mobile Enabled
- Motion Detection
- Email Alerts
- Low Light Mode
- PC/Mac Compatible

**Colour Low-Light View** The camera's brightness settings are automatically adjusted when the room light is dimmed, so you are still able to view video in low light conditions. Furthermore the Y-cam White S POE will superimpose up to 4 images (frame integration) in 1 frame to increase the brightness of the picture.

**Power Over Ethernet** The Y-cam White S POE is equipped with Power over Ethernet support and can receive both power and data over a single Ethernet network cable. This allows the camera to be placed in areas that aren't close to a power outlet and provides quicker, smarter and cost-effective installations.

**Mobile Viewing** With support for MJPEG and 3GPP the camera provides a live view for multiple platforms, including mobile devices such as the iPhone and Blackberry. The Y-cam's live stream can be viewed using any mobile phone that can play VLC-compatible streams, such as Quicktime and RealPlayer.

**Email and FTP alerts** The Y-cam comes with useful alarm tools that will keep you notified if any motion is detected. It has built-in functions that can automatically send an email to you, or upload the video or images straight to a FTP server, meaning that your data will be safely stored offsite.

**PC and Mac Compatible** The Y-cam is fully compatible with both PC and Apple Macintosh computers across multiple web browsers. Mac users can now view live video with audio (using QuickTime), control the motion detection settings within a browser (using Adobe Flash), take snapshots from the live feed, and also record footage locally (using QuickTime Pro).

**Motion Detection** If the Y-cam detects movement in its field of vision, it can automatically send an e-mail alert notifying the owner that motion has been detected, with an attached image of the scene. Unlike conventional activity detection, the Y-cam uses vector information to detect motion, therefore achieving better reliability against false alarms.

**Secure Connection** Make sure your camera is secure using the Y-cam's secure password authentication. Connect your camera to the internet or only on your local network, and access the camera can be restricted to just those with the authenticated password, allowing you to be sure your cameras are only accessed by authorised users.

Please note : The Y-cam White S POE version does not have wireless WiFi capability. Using the PoE capability of the camera requires the use of either a PoE enabled switch/router/hub, or a separate PoE injector to supply power to an Ethernet cable.

## Technical Specifications

### Camera

- Image device 1/4" Prime; CMOS
- Pixels 310,000
- White Balance Auto

# Y-cam White S POE IP Camera

- Exposure mode Auto
- Gain Auto
- Viewing angle Horizontal: 60°; Vertical: 45°;
- Focal length f=3.6mm
- Aperture F2.0mm
- Min.Illumination 1.0 Lux
- Power over Ethernet (PoE) 802.3af

## Network

- Image compression MPEG-4, MJPEG
- Image resolution 640×480(VGA), 320×240(QVGA), 160×120(QQVGA)
- Max. frame rate 30fps @640×480
- Audio compression G.726 (40/32/24/16Kbps)
- Built-in microphone Electret Condenser Microphone
- Simultaneous viewers 16
- Authentication ID/Password, Administrator/General User (Up to 64)
- Network protocols TCP, UDP, IP, ARP, ICMP, DHCP, DNS, HTTP, FTP, SMTP, NTP, PPPoE, DDNSUPnP – Automatic discovery and configuration
- Stream Type RTSP/RTP/RTCP, 3GPP, ASF
- Network connection Ethernet (10BASE-T/100BASE-TX)

## General

- Power requirements DC 5V
- Power consumption 3.25W
- Operating temperature -5 to +45 °C (+22 to +113 °F)
- Storage temperature -20 to +60 °C (-4 to +140 °F)
- Operating humidity 20-80%RH (Non-condensing)
- Storage humidity 20-95%RH (Non-condensing)
- Dimensions(W x D x H) 85mm x 85mm x 30mm
- Weight 150g (Main Body)
- Package Contents Y-Cam White S POE (x1), AC adaptor (x1), Network Cable (x1), Setup CD-ROM (x1), Quick Start Guide (x1), Stand (x1)

## PC system minimum requirements

- Operating system Windows 2000/XP/Vista/Windows 7/Windows 7
- Processor Intel Pentium III, 800MHz or Higher
- Memory 128MB RAM Minimum
- Web browser Most browsers supported. Internet Explorer 5.5 or higher, Mozilla Firefox, Safari,

## Mac system minimum requirements

- Operating system Mac OSX 10.4 Tiger
- Processor 800MHz – PowerPC G4 or Intel
- Memory 128Mb RAM (256Mb or higher recommended)
- Web browser Safari, Mozilla Firefox, Chrome. Most browsers supported

**Price: £131.00**

---