Yealink EXP39 LCD IP Phone Expansion Module



Product Name: Yealink EXP39 LCD IP Phone Expansion Module

Manufacturer: Yealink Model Number: EXP39

Yealink EXP39 LCD IP Phone Expansion Module

The Yealink EXP39 Expansion Module is ideal for receptionists, administrative assistants, call center agents, power users, and executives who need to monitor and manage a large volume of calls on a regular basis. The Yealink EXP39 is designed for improving the power and flexibility of the Yealink SIP-T26P, SIP-T28P and SIP-T38G advanced IP phones. The EXP39 makes for a highly effective assistant to your Yealink IP Phone.

Yealink EXP39 Expansion Module Key Features

- Rich visual experience with 160x320 graphic LCD
- 20 physical keys each with a dual-color LED
- 20 additional keys through page switch
- Daisy-chain 6 modules up to 120 keys
- Supports BLF/BLA, speed dialing, call pickup, etc.

It features a 160x320 graphic LCD and 20 physical keys each with a dual-color LED. With them, you will be very clear which function has been set for easy operation. What's more, you can add 20 additional keys through a page switch, to make the number programmable keys up to 40. Each programmable key supports the functions include speed dialing, BLF/BLA, intercom, call forward/transfer/hold/park/pickup/return etc. Up to 6 EXP39 modules cans be daisy chained.

Yealink EXP39 Expansion Module - Technical Specifications Main Features

- 160x320 graphic LCD with 4-level gray scales
- 20 physical keys each with a dual-color LED
- 20 additional keys through page switch
- Supports up to 6 modules daisy-chain
- Different icons for each function shown on the LCD
- Dual-color LED for status information
- Supports Busy Lamp Field (BLF)
- Bridge Line Appearance (BLA)
- Programmable for speed dialing, call pickup
- Intercom, hold, transfer, voicemail, forward, DND...
- Expansion modules (≤2) are powered by the host phone. Applies to Yealink IP Phone SIP-T28P and SIP-T26P.

Physical Features

2xRJ12(6P6C)ports for data in and out
Power adapter: AC 100~240V input and

DC 5V/3A outputWeight: 290g

Dimensions: 145x182x100mmOperating humidity: 10~90%

Storage temperature: max 40°C

Price: £87.75