

# Yealink T21P IP Phone (SIP-T21P)



Product Name: Yealink T21P IP Phone (SIP-T21P)

Manufacturer: Yealink

Model Number: SIP-T21P

## Yealink T21P IP Phone (SIP-T21P)


Please Note: Yealink T21P phones are PoE (Powered-Over-Ethernet) and do not include a mains Power Supply. If mains power is required, this can be added via the drop down menu above.

The Yealink T21P is a VoIP phone featuring an extra-large 132 x 64-pixel graphical LCD screen, showing a clear 5-line data display. The T21P offers a smoother user experience and visual information at a glance, plus HD Voice characteristics. Dual 10/100 Mbps network ports with integrated PoE are ideal for extended network use.


### Yealink T21P Key Features

- HD Voice: HD Codec, HD speaker, HD handset
- 132 x 64-pixel graphical LCD
- 2 VoIP accounts
- Two-port 10/100 Ethernet Switch, integrated PoE
- Headset Compatible
- Wall-mountable
- XML/LDAP remote phonebook

The T21P supports two VoIP accounts, simple, flexible and secure installation options, plus support for IPv6, Open VPN and a redundancy server. It also operates with SRTP/ HTTPS/ TLS, 802.1x. As a very cost-effective and powerful IP solution, the T21P maximizing productivity in both small and large office environments.



Save time and money with our  
**Redirection & Provisioning Service**



[Learn More](#)



**Yealink VoIP Phones  
Full Comparison Table Guide**



[View Guide](#)

## Yealink T21P VoIP Phone - Technical Specifications

### Audio Features

- Full-duplex hands-free speakerphone with AEC
- Codecs: G.722(Wideband), G.711(A/μ), G.723, G.729AB, G.726
- DTMF: In-band, Out-of-band(RFC 2833) and SIP INFO
- VAD, CNG, AEC, PLC, AJB, AGC

### Directory

- Local phonebook up to 1000 entries

# Yealink T21P IP Phone (SIP-T21P)

- Black list
- XML/LDAP remote phonebook
- Intelligent search method
- Phonebook search/import/export
- Call history: dialed/received/missed/forwarded

## Phone Features

- 2 VoIP accounts
- Call hold, mute, DND,
- One-touch speed dial, hotline
- Redial, call return, auto answer
- Call forward, call waiting, call transfer
- Group listening, SMS
- Local 3-way conferencing
- Direct IP call without SIP proxy
- Ring tone selection/import/delete
- Keypad lock, emergency call
- Set date time manually or automatically
- Dial plan, XML Browser, action URL&action URI

## IP PBX Features

- Anonymous call, anonymous call rejection
- Message waiting indicator (MWI)
- Voice mail, call park, call pickup
- Intercom, paging, music on hold
- Call completion, call recording, hot-desking

## Display and Indicator

- 132x64-pixel graphical LCD
- LED for call and message waiting indication
- Intuitive user interface with icons and soft keys
- National language selection
- Caller ID with name, number

## Network and Security

- SIP v1 (RFC2543), v2 (RFC3261)
- IPv6&#65292;open VPN
- NAT transverse: STUN mode
- Proxy mode and peer-to-peer SIP link mode
- IP assignment: static/DHCP/PPPoE
- HTTP/HTTPS web server
- Time and date synchronization using SNTP
- UDP/TCP/DNS-SRV(RFC 3263)
- QoS: 802.1p/Q tagging (VLAN), Layer 3 ToS, DSCP
- SRTP for voice
- Transport Layer Security (TLS)
- HTTPS certificate manager
- AES encryption for configuration file
- Digest authentication using MD5/MD5-sess
- IEEE802.1X

# Yealink T21P IP Phone (SIP-T21P)

## Management

- Configuration: browser/phone/auto-provision
- Auto provision via FTP/TFTP/HTTP/HTTPS for mass deploy
- Auto-provision with PnP
- Zero-sp-touch
- Provisioning server redundancy supported
- Reset to factory, reboot
- Package tracing export, system log

## Physical Features

- 2xRJ45 10/100M Ethernet ports
- 31 keys including 4 soft keys
- 4 LEDs: 1xpower, 2xline, 1xmessage
- 1xRJ9 handset port
- 1xRJ9 headset port
- Wall-mountable
- Power adapter: AC 100~240V input and DC 5V/600mA Output
- Power over Ethernet (IEEE 802.3af)
- Power consumption: 1.4-2.6W
- Net weight: 0.81kg
- Dimension: 209mm\*188mm\*150mm\*41mm
- Operating humidity: 10~95%
- Storage temperature: -10~50&deg;C

## Package Features

- Qty/CTN: 10 PCS
- N.W/CTN: 10.8KG
- G.W/CTN: 12.3KG
- Giftbox size: 215mm\*200mm\*118mm
- Carton Meas: 615mm\*436mm\*208mm

**Price: £60.09**

Options available for Yealink T21P IP Phone (SIP-T21P) :

### Power Supply Required?

None - Using PoE, UK PSU required (+£3.99), EU PSU required (+£3.99).

### RPS Extension ID

TEXT.

### RPS Extension Password

TEXT.

### RPS Display Name

TEXT.

### RPS PBX URL

TEXT.

# Yealink T21P IP Phone (SIP-T21P)

**RPS NAT Enabled**

[TEXT.](#)

**RPS Outbound Proxy**

[TEXT.](#)

**RPS SIP Port**

[TEXT.](#)

**RPS Enable Outbound Proxy**

**RPS Own Server URL**

**RPS Own Server Name**

VoIPVN <http://voip.com.vn>