

# ZYCOO ZX100-A16610 IP-PBX - 10 x FXO and 6 X FXS



Product Name: ZYCOO ZX100-A16610 IP-PBX - 10 x FXO and 6 X FXS

Manufacturer: ZYCOO

Model Number: ZX100-A16610

ZYCOO ZX100-A16610 IP-PBX - 10 x FXO and 6 X FXS

Please Note: The ZYCOO ZX100 Series has been discontinued. For an alternative, we recommend the ZYCOO CooVox U100 IP PBX.

The ZYCOO ZX100-A16610 IP-PBX - 10 x FXO and 6 X FXS is running based on X86 system with 1U rack-mountable housing case, mainly used for small and medium business. The ZYCOO ZX100-A16610 IP-PBX - 10 x FXO and 6 X FXS ports. Features ZYCOO ZX100-A16610 IP-PBX - 10 x FXO and 6 X FXS

- 80 Concurrent calls
- Up to 1000 registers
- Recording Full Feature IP PBX
- Video Calls
- Multiple Language(English/French/Chinese)
- DID(Direct Inward Dialing Number)
- Support SKYPE for SIP
- Call Monitoring

## Technical Specification

### Key Features

- 80 Concurrent calls
- Up to 1000 registers
- Recording
- Full Feature IP PBX
- Video Calls
- Multiple Language(English/French/Chinese)
- DID(Direct Inward Dialing Number)
- Support SKYPE for SIP
- Call Monitoring

### Basic Features

- Codec: G.711-Ulaw, G.711-Alaw, G.726, G.729, GSM, SPEEX, H.261, H.263, H.263+, H.264
- Call Hold / Forward / Transfer / Waiting / Parking
- Call Paging and Intercom
- Caller ID
- Music On Hold
- DISA(Direct Inward System Access)
- Flexible Dial Plan
- Ring Group
- Conference Room
- Call Logs
- BLF(Busy Lamp Field)
- Configuration By web
- Built-in SIP/IAx2 server
- Build-in voice mail server
- System Backup and Restore

- Echo Cancelation/VAD
- Support Static/DHCP/PPPOE
- VPN Client(Support N2N)
- DDNS Client(Support Dyn dns.org)
- Support NTP(Network Time Protocol)

## Interface

- 1 AC (110V~200V input)
- 1 WAN ports (10/100M)
- 1 Lan ports (10/100M)
- 16 RJ11 (FXS/FXO) -- Model: ZX100-A16
- 1 PRI -- Model:ZX100-E1

## Hardware

- CPU: ATOM N270, 1.6 GHz x86 CPU
- RAM: 2 GB DDR2 RAM
- Storage: 320 mobile hard disk drive
- PSU: 300W Power Supply with industry standard
- Dimensions: W: 465 mm, H: 44.5 mm , D: 370 mm
- Rack mountable: Comes with accessories
- Weight: 7.0Kg

## Environmental requirements

- Temperature: -10&deg;C-45&deg;C
- Storage temperature: -30&deg;C-65&deg;C
- Humidity: 10-80% no dew
- Power: AC100~240V

**Please Enquire**

---