Product Name: beroNet BN2S0mini Asterisk Mini-PCI Card (2 BRI ISDN ports)
Manufacturer: beroNet
Model Number: BN2S0mini

Availability: Discontinued
Please note that this product has been discontinued. We recommend the beroNet Berofix Gateways as a good alternative. beroNet BN2S0mini Asterisk Mini-PCI Card; 2 BRI ISDN ports beroNet is providing with the BNXS0mini a 1 Port, 2 Port and a 4 Port ISDN BRI card, a powerful and flexible solution for small and embedded ISDN Appliances based on the Open Source PBX Asterisk. The BNXS0mini BRI Card series consists of a miniPCI form factor card and an addon Board, where the BRI Ports are carried out. The addon Board can be customized to your requirements on your Appliance-chasis. Together with our channel-driver "chan_mISDN", which is covered by the GPL licensing agreement, you can easily add BRI ports to your Asterisk system. Our channel-driver is based on the new ISDN stack of the new Linux Kernel: mISDN (modular ISDN). The BNXS0mini card series is available with 1, 2 or 4 S0 ports, which can be configured individually for each port for NT (Network Termination) or for TE (Terminal Equipment) mode. In either mode the card supports Point-To-Multi-Point mode or Point-To-Point mode. Features

• 1, 2 or 4 BRI Ports
• Each port can be configured individually for TE / NT mode
• L1, L2, L3 tested (TE-Mode) for compliance to European standards forEuroISDN
• Hardware DTMF Detection
• ISDN ports are short-circuit protected (by electronic fuse, auto-reset)
• Line termination (100 ohms) is selectable for each port by DIP switch
• Suitable for miniPCI Slots

Please Enquire