

Escene WS290 is a highly innovative based wireless IP phone, It can perfectly satisfy with all kinds of the businessman communication. WS290 integrates with 128x64 graphic LCD, a large resolution display screen, elegant and intuitive user interface, which indicate you can enjoy perfect user experience.WS290 offers high audio quality HD handset, HD speaker and HD codec (G.722), with a rich set of business communication features that can definitely improve working efficiency and sense. Escene WS290 is highly suitable for SMEs, Home Office and ISP applications.

Key Features

- 128*64 Graphic LCD.
- HD Voice: HD Codec, HD Speaker, HD Handset.
- Multi-language: Chinese, English, French, Russian, etc.
- 2 level adjustable bracket and wall-mountable.
- Two SIP accounts and support three-way conference, SMS.
- 1xRJ45 port, 3.5mm and RJ9Headset.
- USB port for external unit charging.
- Auto-provision, HTTP/TFTP/FTP, Tr069. XML/LDA, Contact Search.
- Connect to the wifi network without cable.



WS290 Technical Datasheet

Phone Features

2 SIP accounts, Hotline Call hold, Call waiting, Call forward, Call return Call transfer (blind/busy/ask) Caller ID display, Redial, Mute, DND Auto-answer, 3-way conferencing Speed dial, SMS, Voicemail Message Waiting Indication LED Tone scheme. Volume control Direct IP call without SIP proxy Ring tone selection/import/delete Phonebook (Personal Phone Book Search/Input/Output (300 entries), Black list, Hand-free indicator. Call history: dialed/received/missed (100 -entries); One-key back (C) Multi-Language (2aB/abc/ABC/123) Soft keys programmable, Supports PC control Support switching SIP server & Second server

Advanced Features

XML Phone Book search and input & output Enterprise phone book(800 entries) LDAP phone book Functions customizable keys

IP PBX System Integration

Busy lamp field (BLF), BLF list Bridged line appearance (BLA) DND & Forward synchronization Intercom, Paging, Music on hold Call pickup, Dial Plan, Call recording Anonymous call, Anonymous call rejection Network conference, Distinctive ringtone

Security

802.1x, VLAN QoS (802.1pq) Transport Layer Security (TLS) Digest authentication using MD5/MD5-sess Secure configuration file via AES encryption Phone lock for personal privacy protection Admin/VAR/User 3-level configuration mode

Network Features

SIP v1 (RFC2543), v2 (RFC3261) SIP connection: Proxy mode & Peering Points mode DNS SRV (RFC3263) Redundant server support NAT Traversal: STUN mode DTMF: In-Band, RFC2833, SIP Info, Auto HTTP/HTTPS Web Management IP Assignment: Static/DHCP/PPPoE Bridge/Router mode for PC port TFTP/DHCP/PPPoE client Telnet/HTTP/HTTPS server DNS client, NAT/DHCP server WIFI: 802.11b/g/n

Management

Auto-provision via FTP/TFTP/HTTP/HTTPS SNMP V1/2 , TR069 Configuration: browser/phone/auto-provision Trace package and system log export

Codes and Voice Features

Wideband Codec: G.722 Narrowband codec: G.711µ/A, G.723.1 G.726, G.729AB,VAD, CNG, AEC, AGC Full-duplex,

Physical Features

128x64 graphic LCD 33 keys including 2 programmable keys 1x3.5mm handset port,1xRJ9 headset port 1xRJ45 10/100M Ethernet ports 2 level adjustable bracket and wall-mountable Power adapter: AC 100~240V input and DC 5V/1A output Power consumption: 1.4-2.6W Net weight: 0.80KG Dimension: 185x200x90MM Operating humidity: 10~95% Storage temperature: up to 60°C

Package Features

Qty/CTN: 10 PCS N.W/CTN:12.50 KGS G.W/CTN: 13.50KGS Measurement: 0.068CBM(0.5% more or less) Carton Meas: 500x480x320MM

Certifications



දි) ISO 9001

Compatible with the platform



Escene Communication Co.,Ltd

Address: Floor 4 Building C YueAn Industrial Park No.51 Huangcun Road Tianhe District, Guangzhou, China. Postal Code: 510665 Tel: (+86)20-28096798 Fax:(+86)20-28096786